

JUNO 300

EMERGENCY TWIN SPOT NON-MAINTAINED

JUNO 300 is the ideal solution for adjustable, non-maintained emergency lighting. The high light output suits higher mounting applications and where flexibility is a prime consideration.



Features

- Tough IK06 construction
- Fully adjustable LED projector flood heads
- 120° beam angle
- Fast and easy to install



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
JUN/300	Juno NM Emergency Twin Spot 3 Hr 300lm IP21	300 lm	300 lm	2.2W	135 lm/W

Product Information

Guarantee	5 Years
Emergency Battery Guarantee	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	6500K
IP Rating	IP20
IK Rating	IK06
Emergency Battery Type	LiFePO4
Voltage	220-240V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate

Colour Rendition (CRI)	>80
Colour Finish	White RAL9003
LED Life Expectancy	36000hours
Power Factor	>0.3
Frequency	50/60Hz
Driver Type	Fixed
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	0°C to +45°C
EM Working Temperature	0°C to +45°C

JUNO 300

EMERGENCY TWIN SPOT NON-MAINTAINED

Packaging Information

Dimensions (mm)	L: 275 x W: 269 x D: 61 mm
Product Net Weight (kg)	0.7 kg
Barcode	5055807624428
Box Dimensions (mm)	L: 277 x W:290 x D: 64 mm
Box Gross Weight (kg)	0.82 kg

Units/Outer Carton	10
Outer Carton Barcode	15055807624425
Outer Carton Dimensions (mm)	L: 570 x W: 345 x D: 305 mm
Outer Carton Gross Weight (kg)	8.9 kg

